

PS-32

Full featured, lightweight and easy to operate

Entry model. Easy operation, fitted with professional features. Very easy starting.



Easy Start: Spring assisted starter combined with optimized engine management



Touch&Stop one lever operating



Fuel pump (Primer)



Metal spike bar

Technical specifications

Displacement	32 cc (1.95 cu. in)	Chain tensioning	Lateral tensioning
Power rating	1.35 kW (1.8 HP)	Automatic oilpump	yes
Max engine speed	12,800 rpm	Catalytic converter	yes
Net weight	4.1 kg (9.02 lbs)	Standard guide bar	14"
Fuel tank capacity	0.4 l (13.5 oz)	Optional guide bars	16"
Oil tank capacity	0.28 l (9.5 oz)	Chain pitch	3/8 "
Vibration damping	yes	Chain gauge	.050 "

- Easy Start: Spring assisted starter combined with optimized engine management significantly reduces resistance
- Touch&Stop one lever control with clearly defined positions for cold starting, operation and stop. Engines shuts off with just a touch.
- Primer pump
- MPI technology (Memory-Power-Ignition) for easy restart
- Metal spike bar as standard
- SafetyMatic chain brake.
- Professional quality centrifugal clutch
- Outside sprocket
- Adjustable metal oil pump
- Catalytic converter to clean the exhaust gases
- Big tank cap, easy reachable. S-form with acme thread for easy operation
- 33 cm markings on the rear handle for cutting wood to length
- 4 steel springs for low vibration
- Lateral chain tensioning
- Two bar studs for reliable bar fastening

DOLMAR Power Products • PO Box 5007 • Alpharetta, GA 30023-5007

www.dolmarpowerproducts.com

www.dolmar.com

