

# PS-6100



This chainsaw does the job as a felling saw and a debranching saw in one machine. Especially at far offsite locations which have to be reached by foot, the transport of only one saw makes the job a lot easier.



Touch&Stop one lever control with clearly defined positions for cold starting, operation and stop. Engines shuts off with just a touch.



Primer pump for easy cold start



Extended worktime with Longlife Filter system. Toolless change and easy cleaning.



Easy Start: Spring assisted starter

Technical specifications			
Displacement	61 cc (3.7 cu. in)	Vibration damping	yes
Power rating	3.4 kW (4.5 HP)	Chain tensioning	Lateral tensioning
Max engine speed	13,800 rpm	Automatic oilpump	yes
Net weight	6.0 kg (13.22 lbs)	Standard guide bar	PHO
Fuel tank capacity	0.8 l (27 oz)	Optional guide bar	18", 20"
Oil tank capacity	0.48 l (16.2 oz)		

- Big fuel tank - up to 30 minutes operating with one tankfill
- Intake air pre-cleaning significantly reduce dirt particles at an early stage
- Extended worktime with Longlife Filter system. Toolless change and easy cleaning.
- Easy Start: Spring assisted starter combined with optimized engine management significantly reduces resistance
- Primer pump for easy start
- MPI technology (Memory-Power-Ignition) for easy restart
- Up to 20% less fuel consumption and low emissions according 2002/88/EC for environmental and user benefit with SAS-Technology
- Touch&Stop one lever control with clearly defined positions for cold starting, operation and stop. Engines shuts off with just a touch.
- Powerful at a high torque
- Vibration damping
- Lateral chain tensioner for uncomplicated re-tensioning of the saw chain
- Adjustable oil pump, disabled at engine idling
- Centrifugal clutch with 3 weights
- SafetyMatic chain brake

DOLMAR Power Products . PO Box 5007 . Alpharetta, GA 30023-5007

www.dolmarpowerproducts.com

www.dolmar.com

