

PS-6400

Powerful chain saw for professional users

Power, torque and light weight - just what the professional chain saw operator requires for efficient and low-effort forestry work such as tree felling and stripping.



Lateral chain tensioning



Optimum chip exhaust for avoiding jams



Easy filter maintenance



Low starting effort with decompression valve

Technical specifications

Displacement	64 cc (3.9 cu. in)	Chain tensioning	Lateral tensioning
Power rating	3.5 kW (4.7 HP)	Automatic oilpump	yes
Max engine speed	13,500 rpm	Handle Heating	no
Net weight	6.4 kg (14.1 lbs)	Standard guide bar	Power head only
Fuel tank capacity	0.75 l (25.36 oz)	Optional guide bar	20, 24, 28, 32
Oil tank capacity	0.42 l (14.20 oz)	Chain pitch	3/8 "
Vibration damping	yes	Chain gauge	.050 "

- Proven reliability
- Tool-less filter maintenance
- Integrated chain brake
- Vibration damping
- Lateral chain tensioning
- Decompression valve
- Optimum chip flow through
- Adjustable oil pump, disabled at engine idling

DOLMAR Power Products • PO Box 5007 • Alpharetta, GA 30023-5007

www.dolmarpowerproducts.com

www.dolmar.com

